




Orthomat® Ultimate

Can be used in areas with oil, water or chemical spillage

- Exclusive PolyNit outer layer encapsulates entire mat.
- PolyNit seals unlike laminated products for outstanding durability.
- Soft foam inner layer cushions impact from standing to delay fatigue.
- High density composition gives essential underfoot support and shape recovery.
- Neat, tapered edges are heat-sealed using specialist technology developed by COBA Europe.
- Robust ramped edges limit trip hazard.
- Textured surface traps dry debris or swarf.



Technical Specification

Material:	Virgin Closed Cell PVC (Foam) with PolyNit outer (fusion bonded, not glued)
Surface Finish:	Diamond pattern
Product Height:	10mm
Roll Length:	18.3m
Operating Temperature:	0°C to +55°C
Resistant to Chemicals:	In tests conducted by COBA, Orthomat® Ultimate showed no visible signs of corrosion or damage when fully submerged in both of the following chemicals: Castrol Alpha SP 320 Industrial Extreme Pressure Gear Oil and Pac 89 Phosphoric Acid Cleaner
Environmental Resistance:	Suitable for wet and dry indoor environments
Installation Method:	Loose lay
Cleaning Method:	Brush/Mop the top surface
Product Performance:	Conforms to Slip Resistance Test DIN 51130: 2010 Category R11
Flame Retardancy:	Conforms to BS EN ISO 11952-2:2002, Class Efl. Conforms to BS EN ISO 9239-1:2002, Class Class DflS1

Country of Origin:	China
Guarantee:	3 year guarantee for normal to moderate use

Sizes	Black	Weight
0.6m x 0.9m	OU010001	2.92 kg
0.9m x 1.5m	OU010002	7.29 kg
0.9m x 18.3m	OU010003	89.00 kg
0.9m x per linear metre (max. 18.3m)	OU010003C	3.00 kg