



tesa[®] Masking Tape Standard

BNR 5061, 5062, 5085, 5086, 5087, 5088, 5089, 56550, 56551, 56552, 56553, 56554, 59005, 59006, 59007

Product Features

- Good adhesive strength on most surfaces
- 3 days residue-free removal
- Solvent-free

Product Description

tesa[®] Masking Tape Standard is a multi-functional masking tape that should always be part of the equipment if you decide to paint a wall or renovate your home.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------------|--------------------|----------------|
| • Total thickness | 110 µm | • Type of adhesive | natural rubber |
| • Backing material | slightly-creped paper | | |

Properties/Performance Values

- | | | | |
|------------------------|--------|-----------------------------------|---------|
| • Residue free removal | yes | • Tensibility | 10 % |
| • Area of use | Indoor | • Tensile strength | 33 N/cm |
| • Solvent free | yes | • Hand tearability | yes |
| • Tear resistance | yes | • Residue-free removable after... | 3 days |
| | | | days |

tesa[®] Masking Tape Standard

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=05061>