

EODD 2388/8661

1/5

Creation Date : May 7, 2001  
Revision Date : February 21, 2006

# Safety data sheet for chemical products

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: UB-150 Black [ uni-ball eye ]

Creation Date : May 7, 2001  
Revision Date : February 21, 2006  
File No. : 066117A Rev. 2.5.02.02

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

The chemical product is a substance or a preparation : Preparation

Chemical nature: Component parts : Ink

Chemical or generic name	CAS No.	TSCA	EINECSNo.	Concentration range (wt%)
Water	7732-18-5	Registered	2317912	50- 80
Glycerine	56-81-5	Registered	2002896	< 10
1,2-Propanediol	57-55-6	Registered	2003380	< 10
Diethylene glycol	111-46-6	Registered	2038722	< 10
Carbon Black	1333-86-4	Registered	2156099	< 10
Resins	Registered	Registered	Polymer	< 10

Other parts : Other parts are excluded from 'chemical substances'.

## 3. HAZARDS IDENTIFICATION

Most important hazards : Not available.

Specific hazards : Information of components.

&lt;Carbon Black&gt;

MAJOR HEALTH HAZARDS: suspect cancer hazard (in animals)

## 4. FIRST-AID MEASURES

Inhalation:

Not applicable.

(Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

Skin contact:

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Eye contact:

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion:

If swallowed, seek medical advice, and show the MSDS to the physician then.

[Ink quantity of product : about 2.1g]

-UB-150 Black-

---

## 5. FIRE-FIGHTING MEASURES

---

Fire and explosion measures : Slight fire hazard.

Extinguishing media:

- Suitable : regular dry chemical, carbon dioxide, water, regular foam.
- Large fires : Use regular foam or flood with fine water spray.
- Fire fighting : Move container from fire area if it can be done without risk.  
Use extinguishing agents appropriate for surrounding fire.  
Avoid inhalation of material or combustion by-products.  
Stay upwind and keep out of low areas.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

- Personal precautions : Not available.
- Environmental precautions : Do not wash away into shower or water way.
- Methods for cleaning up : Wipe off by dry cloth and wash with water.  
: In accordance with national, state and local regulations.

---

## 7. HANDLING AND STORAGE

---

Store and handle in accordance with all current regulations and standards.  
Keep separated from incompatible substances.

Handling:

- Technical measures : Don't swallow ink.  
: Rccap after use.  
: Don't shake.  
: Keep out of the reach of children.  
: Avoid contact with skin and eyes.

- Precautions : Not available.
- Safe handling advice : Not available.

Storage:

- Technical measures : Keep away from oxidizing materials, ignition sources and high temperature.
- Storage condition : Avoid direct sunlight.  
: Do not leave the products in high temperature space.  
: Recommended temperature: 0-30 C.

Incompatible products : (Information of components.)

- |   |                   |
|---|-------------------|
| acids, bases, oxidizing materials, metal oxides, peroxides,<br>reducing agents                                  | Glycerine         |
| acids, bases, combustible materials, halo carbons, metals,<br>metal salts, oxidizing materials, reducing agents | 1,2-Propanediol   |
| acids, bases, oxidizing materials   | Diethylene glycol |
| oxidizing materials, halogens   | Carbon Black      |
| strong acids, alkalies, oxidizers, oxidizing materials  | Resin             |

Packaging materials : Not applicable.

3/5

Creation Date : May 7, 2001  
Revision Date : February 21, 2006**8. EXPOSURE CONTROL / PERSONAL PROTECTION**

Engineering measures : Not required.

Control parameters (Information of components.)

OSHA	3.5mg/m <sup>3</sup> 5mg/m <sup>3</sup> TWA(respirable dust fraction), 15mg/m <sup>3</sup> TWA(total dust)	Carbon Black Glycerine
ACGIH	3.5mg/m <sup>3</sup> (total dust) 10mg/m <sup>3</sup> TWA	Carbon Black Glycerine
EC	3.5mg/m <sup>3</sup>	Carbon Black
DFG	44 mg/m <sup>3</sup> (10ml/m <sup>3</sup> ) MAK(peak limitation category-II, 2)	Diethylene glycol
UK	150ppm(474mg/m <sup>3</sup> ) TWA(total(vapor and particulates)), 10mg/m <sup>3</sup> TWA(particulates)	1,2-Propanediol

Personal protective equipment : Not required.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

[ ] : Information of components.

Physical state and form	: Low viscous liquid.
Colour	: Black.
Odour	: None odour.
pH	: 8.5±0.5
Boiling point	: Not available. [Water/ 100 C]
Melting point	: <-10 C
Flash point	: Not applicable. [1,2-Propanediol/ 99 C]
Autoignition temperature	: Not applicable. [Diethylene glycol/ 224 C]
Explosion limits	: Not applicable. [ Lower flammable limit / 2.6% , Upper flammable limit / 12.5% <1,2-Propanediol> ]
Density	: about 1.1 / 25 C
Vapour density (air=1)	: Not available. [1,2-Propanediol/ 2.60-2.62]
Solubility in water	: Soluble.
Evaporation rate	: Not available.
Volatile	: 84-87%

**10. STABILITY AND REACTIVITY**

Stability : Stability.

Hazardous reactions : Will not occur.

Conditions to avoid : Avoid heat, flames, sparks and other sources of ignition.  
Avoid contact with incompatible materials.

Materials to avoid : (Information of components.)

oxidizing materials, halogens	Carbon Black Glycerine
acids, bases, oxidizing materials, metal oxides, peroxides, reducing agents	
acids, bases, combustible materials, halo carbons, metals, metal salts, oxidizing materials, reducing agents	1,2-Propanediol
acids, bases, oxidizing materials	Diethylene glycol
strong acids, alkalies, oxidizers, oxidizing materials	Resin



4/5

Creation Date : May 7, 2001

Revision Date : February 21, 2006

Hazardous decomposition products : (Information of components.)  
 oxides of carbon, water common decomposition products  
 oxides of sulfur. Carbon Black  
 corrosive acrolein. Glycerine  
 oxides of nitrogen. Resin

## 11. TOXICOLOGICAL INFORMATION

(Information of components)

Acute toxicity

Ingestion LD50	>10000mg/kg-Rat 4090mg/kg-Mouse 20000mg/kg-Rat 3300mg/kg-Cat, 7800mg/kg-Guinea pig	Carbon Black Glycerine 1,2-Propanediol Diethylene glycol
Inhalation LC50	>570mg/m <sup>3</sup> -1H-Rat	Glycerine
Skin LD50	>3000mg/kg-Rabbit >10000mg/kg-Rabbit 20800mg/kg-Rabbit 11890mg/kg-Rabbit	Carbon Black Glycerine 1,2-Propanediol Diethylene glycol

Local effects

Irritant:inhalation, skin  
Irritant:skin  
Carbon Black  
Diethylene glycol

Chronic toxicity and long term toxicity

Respiratory disorders. Carbon Black  
Repeated or prolonged contact may cause skin sensitization. 1,2-Propanediol

Signs and Symptoms of overexposure and aggravated by exposure

Inhalation	irritation irritation,difficulty breathing nausea,headache nausea,cough	Carbon Black / Resin Glycerine 1,2-Propanediol Diethylene glycol
Skin contact	irritation irritation,redness irritation,allergic reaction	Carbon Black / Resin Glycerine / Diethylene glycol 1,2-Propanediol
Eye contact	mechanical irritation, discoloration of lids tearing,stinging irritation,pain irritation,redness irritation	Carbon Black  Glycerine 1,2-Propanediol Diethylene glycol Resin
Ingestion	nausea,vomiting allergic reaction,vomiting	Glycerine / Diethylene glycol 1,2-Propanediol

Specific effects

IARC Group 2B  
Carbon Black

## 12. ECOLOGICAL INFORMATION

Not available.

5/5

Creation Date : May 7, 2001  
Revision Date : February 21, 2006**13. DISPOSAL CONSIDERATIONS**

Waste from residues : Disposal in accordance with all current regulations and standards.  
Contaminated packaging: Not applicable.

**14. TRANSPORT INFORMATION**

HS Code : 960810

**15. REGULATORY INFORMATION**

Regulations (Information of components)  
Hazardous chemicals (OSHA HCS) : Carbon Black / Glycerine  
EU labeling  
25<=Xn;R22 : Diethylene glycol  
R22 : Harmful if swallowed.  
CANADA Hazardous Products Act - Ingredient Disclosure List  
1%over : Carbon Black / 1,2-Propanediol

**Hazard and safety information**

Products are manufactured in accordance with European regulation EN71 part 3  
Products are manufactured in accordance with ELV directive of EU.

**16. OTHER INFORMATION**

This sheet completes the technical sheet of use but it doesn't replace it.  
The information contained in this sheet are based knowledge of the products  
at the data : (February 21, 2006). They are given quite sincerely.  
Moreover the attention of the users is drawn on the risks possibly taken,  
when a product is used for other utilization than these which it is intended.