



## ART. 4025 Packaging Tape



- Ideal for manual and dispenser applications
- No Noise Unwinding
- Completely solvent free

Material Informations		
Support	ВОРР	
Adhesive	Acrylic Water-Based	
Available Colours	Brown, Transparent, Yellowish, White	
Available Widths	38, 48, 50, 75 (mm)	
Available Lengths	50, 66, 100, 132, 180 (m)	

Technical Informations			
Support Thickness	25 mμ	± 3%	
Total Thickness	42 mµ	± 6%	
Adhesion to Steel Plate	220 gr/cm	± 10%	
Tensile Strength	4,0 Kg/cm	± 10%	
Elongation	150%	± 10%	

## **Storage Conditions**

- We recommend a storage temperature between 18 and 30 °C.
- The product should not be directly exposed to heat or humidity.
- The product should be conditioned to room temperature before use.

All the above mentioned values in Technical Informations are to be considered as avarage values of our standard production and cannot be taken as product specifications.

The products can present a ±2% tolerance in width and length.

We recommend all our customers to make sure that the products is acceptable through preliminary test.

Certified Systems UNI-EN ISO 9001:2008 n° IT244111 UNI-EN ISO 14001:2004 n° IT246656 UNI-EN ISO 18001:2007 n° IT249944 REGISTRATION EMAS n°IT001596



