



Color Copy - the professional paper guarantees you needle-sharp printouts and brilliant colour reproduction, especially with digital colour laser printing. It is perfectly suitable for documents such as presentations, direct mailings, manuals, corporate plans, business cards and envelopes. Now CO2 neutral!









Technical Data: Color Copy

	ISO 536	90		100		120		160		200	200		220	
g/m²		90	± 3.0	100	± 4.0	120	± 4.5	160	± 6.0	200	± 6.0	220	± 6.0	
μm	ISO 534	98	± 4	106	± 4	126	± 4	166	± 6	200	± 7	220	± 7	
sec	ISO 5627	105	± 25	105	± 25	105	± 25	105	± 25	105	± 25	105	± 25	
%	ISO 2471	94.0	± 2	95.0	± 2	96.5	± 2	98.5	± 2	99.0	± 1	99.0		
%	ISO 287	5.0	± .6	5.0	± .6	5.0	± .6	5.0	± .6	5.2	± .6	5.5	± .6	
%	ISO 2470	110.0	± 1.5	110.0	± 1.5	110.0	± 1.5	110.0	± 1.5	110.0	± 1.5	110.0	± 1.5	
%	ISO 11475	161	± 3.0	161	± 3.0	161	± 3.0	161	± 3.0	161	± 3.0	161	± 3.0	
	μm sec % %	μm ISO 534 sec ISO 5627 % ISO 2471 % ISO 287 % ISO 2470	g/m² ISO 536 90 μm ISO 534 98 sec ISO 5627 105 % ISO 2471 94.0 % ISO 287 5.0 % ISO 2470 110.0	g/m²ISO 53690 ± 3.0 µmISO 53498 ± 4 secISO 5627105 ± 25 %ISO 247194.0 ± 2 %ISO 2875.0 $\pm .6$ %ISO 2470110.0 ± 1.5	g/m²ISO 53690 ± 3.0 100µmISO 53498 ± 4 106secISO 5627105 ± 25 105%ISO 247194.0 ± 2 95.0%ISO 2875.0 $\pm .6$ 5.0%ISO 2470110.0 ± 1.5 110.0	g/m² ISO 536 90 ± 3.0 100 ± 4.0 µm ISO 534 98 ± 4 106 ± 4 sec ISO 5627 105 ± 25 105 ± 25 % ISO 2471 94.0 ± 2 95.0 ± 2 % ISO 287 5.0 $\pm .6$ 5.0 $\pm .6$ % ISO 2470 110.0 ± 1.5 110.0 ± 1.5	g/m² ISO 536 90 ± 3.0 100 ± 4.0 120 µm ISO 534 98 ± 4 106 ± 4 126 sec ISO 5627 105 ± 25 105 ± 25 105 % ISO 2471 94.0 ± 2 95.0 ± 2 96.5 % ISO 287 5.0 $\pm .6$ 5.0 $\pm .6$ 5.0 % ISO 2470 110.0 ± 1.5 110.0 ± 1.5 110.0	g/m² ISO 536 90 ± 3.0 100 ± 4.0 120 ± 4.5 µm ISO 534 98 ± 4 106 ± 4 126 ± 4 sec ISO 5627 105 ± 25 105 ± 25 105 ± 25 % ISO 2471 94.0 ± 2 95.0 ± 2 96.5 ± 2 % ISO 287 5.0 $\pm .6$ 5.0 $\pm .6$ 5.0 $\pm .6$ % ISO 2470 110.0 ± 1.5 110.0 ± 1.5 110.0 ± 1.5	g/m² ISO 536 90 ± 3.0 100 ± 4.0 120 ± 4.5 160 µm ISO 534 98 ± 4 106 ± 4 126 ± 4 166 sec ISO 5627 105 ± 25 105 ± 25 105 ± 25 105 % ISO 2471 94.0 ± 2 95.0 ± 2 96.5 ± 2 98.5 % ISO 287 5.0 $\pm .6$ 5.0 $\pm .6$ 5.0 $\pm .6$ 5.0 % ISO 2470 110.0 ± 1.5 110.0 ± 1.5 110.0 ± 1.5 110.0 ± 1.5	g/m² ISO 536	g/m² ISO 536 90 ± 3.0 100 ± 4.0 120 ± 4.5 160 ± 6.0 200 µm ISO 534 98 ± 4 106 ± 4 126 ± 4 166 ± 6 200 sec ISO 5627 105 ± 25 1100	g/m² ISO 536 90 ± 3.0 100 ± 4.0 120 ± 4.5 160 ± 6.0 200 ± 6.0 µm ISO 534 98 ± 4 106 ± 4 126 ± 4 166 ± 6 200 ± 7 sec ISO 5627 105 ± 25 105 ± 25 105 ± 25 105 ± 25 % ISO 2471 94.0 ± 2 95.0 ± 2 96.5 ± 2 98.5 ± 2 99.0 ± 1 % ISO 287 5.0 $\pm .6$ 5.0 $\pm .6$ 5.0 $\pm .6$ 5.0 $\pm .6$ 5.2 $\pm .6$ % ISO 2470 110.0 ± 1.5 110.0 ± 1.5 110.0 ± 1.5 110.0 ± 1.5	g/m² ISO 536 90 ± 3.0 100 ± 4.0 120 ± 4.5 160 ± 6.0 200 ± 6.0 220 ± 6.0 pm ISO 534 98 ± 4 106 ± 4 126 ± 4 166 ± 6 200 ± 7 220 sec ISO 5627 105 ± 25 110.0 ± 1.5 110.0	

Product meets EN 12281, requirements for copy paper for dry toner imaging processes and ISO 9706, requirements for permanence for paper. Production processes certified according to ISO 9001, ISO 14001 and OHSAS 18001. Standard measurement uncertainty between laboratories is not incorporated.

SIGNIFICANCE OF VALUES: 2 SIGMA

TECHNICAL CUSTOMER SERVICE 19.07.2017