



## Elipse® Half Mask with A2P3 Filters


**EURO S.A.L.D.**  
Welding Technology

**DISTRIBUTORE**

+39 049 9485180



H: 130 mm D: 117 mm W: 195 mm



H: 110 mm D: 68 mm W: 69 mm

### Standards

Facemask EN 140:1998  
Cartridge filter  
EN 14387:2004+A1:2008 A2P3 R D

### Weight


Mask + Filters: S/M 288 g, M/L 295 g  
Filters: 204 g

### Shelf Life

5 years (mask & filters). See storage conditions on Instructions for Use.  
Filters are re-usable and changeable.

### Efficiency

P3 >99,95% for 0,3 µ particulate  
At 5000 ppm:  
> 35 minutes Cyclohexane (C<sub>6</sub>H<sub>12</sub>)



**Patent Pending**

1. Particulate pleated filter (total length 645 mm)
2. Activated carbon treated for gas adsorption

3. Designed to help airflow diffusion and full usage of the activated carbon
4. Inhalation valve

### Material

- Inner mask body in Medical Grade TPE
- Covers in PP/ABS
- Valve body in nylon with silicone diaphragms
- Gas filters: Activated carbon sealed into ABS shell

- Particulate filters: Mechanical type multi-layer HESPA synthetic media encapsulated with TPE. Particulate filters are integrated with the carbon element



Comes with **life extender** protective caps

Part #		Description
SPR213L (S/M) SPR223L (M/L)		Elipse® A2P3 Respirator Package also includes: ■ Replaceable filters
FIL253L		Elipse® A2P3 Replacement Cartridges Pair
SPM009		Elipse® Carry Case
SPM646		Elipse® Fit Test Adaptor

## Applications



**Welding & Grinding:** metal fumes and dust in confined spaces (gas welding)



**Constructions:** paint, moulds



**Manufacturing:** solvents, various organic gases



**Automotive & Marine:** coal dust, silica dust



**Agriculture:** pesticides