

Scheda tecnica

CARATTERISTICHE TECNICHE

Power over Ethernet (PoE)	Si
Gestione	Layer 2+
Supporto Routing (Layer 3)	No
Nr. porte PoE	24
Vlan supportate	4093
Industriale	No
Stackable	No
PoE Budget	1440 W
Attacco su barra DIN	No
Quality Of Service (QoS)	Si
Modalità Stacking	No
Dimensioni tabella MAC	16000
Standard PoE supportati	15,4W, 30W
Altre caratteristiche tecniche	24-port 10/100/1000BASE-T (RJ45) Ultra90 PoE++ with 1,440W PoE budget 2-port 10/100/1000BASE-T (RJ45) 4-port 1000BASE-X (SFP) Compatible 802.3af (15.4W), 802.3at (30W), 802.3bt (60, 75 and 90W) 2 internal, fixed PSUs (C14 inlets) with embedded RPS/EPS function When one PSU is used, PoE budget is 720W When two PSU are used, PoE budget is 1,440W 60 Gbps non-blocking fabric across 30 ports Out-of-band 1G Ethernet management port USB-C and RJ45 RS232 console ports and USB-A storage port Front black display panel and all ports in the back Possible reversed mounting with ports in the front Rack-mounting standard brackets Longer brackets for recessed mounting (2 inches / 5 cm) Threaded hole in front (1xM10) for clamps Threaded holes on the bottom (4xM5) for 50x100mm VESA plates Selectable fan modes for quiet or cool operation Dimensions (WxDxH): 440 x 43.2 x 400 mm Weight: 6.75Kg (14.87lb)
Nr. slot	0
Management ridondata	No

CARATTERISTICHE FISICHE

Rack-Mountable	Si
Larghezza	440 mm
Nr. unità rack	1
Profondità	400 mm
Altezza	44 mm
Peso	6750 gr
Altre caratteristiche	24-port 10/100/1000BASE-T (RJ45) Ultra90 PoE++ with 1,440W PoE budget 2-port 10/100/1000BASE-T (RJ45) 4-port 1000BASE-X (SFP) Compatible 802.3af (15.4W), 802.3at (30W), 802.3bt (60, 75 and 90W) 2 internal, fixed PSUs (C14 inlets) with embedded RPS/EPS function When one PSU is used, PoE budget is 720W When two PSU are used, PoE budget is 1,440W 60 Gbps non-blocking fabric across 30 ports Out-of-band 1G Ethernet management port USB-C and

fisiche RJ45 RS232 console ports and USB-A storage port Front black display panel and all ports in the back Possible reversed mounting with ports in the front Rack-mounting standard brackets Longer brackets for recessed mounting (2 inches / 5 cm) Threaded hole in front (1xM10) for clamps Threaded holes on the bottom (4xM5) for 50x100mm VESA plates Selectable fan modes for quiet or cool operation Dimensions (WxDxH): 440 x 43.2 x 400 mm Weight: 6.75Kg (14.87lb)

ALIMENTAZIONE

Power Supply AC
 Alimentatore incluso Si
 Alimentazione ridondata No
 Consumo energetico 1734 W
 Tipologia di alimentazione Nessuna ridondanza di alimentazione
 ridondata

CONNETTIVITÀ

Nr. porte LAN 26 N
 Tipo e velocità porte LAN RJ-45 10/100/1000

Nr. porte Uplink 4
 Tipo e velocità porte Uplink SFP 1GbE

Porta Console Si

Nr. porte fruibili contemporaneamente (LAN + Uplink) 30

Altre informazioni sulla connettività 24-port 10/100/1000BASE-T (RJ45) Ultra90 PoE++ with 1,440W PoE budget 2-port 10/100/1000BASE-T (RJ45) 4-port 1000BASE-X (SFP) Compatible 802.3af (15.4W), 802.3at (30W), 802.3bt (60, 75 and 90W) 2 internal, fixed PSUs (C14 inlets) with embedded RPS/EPS function When one PSU is used, PoE budget is 720W When two PSU are used, PoE budget is 1,440W 60 Gbps non-blocking fabric across 30 ports Out-of-band 1G Ethernet management port USB-C and RJ45 RS232 console ports and USB-A storage port Front black display panel and all ports in the back Possible reversed mounting with ports in the front Rack-mounting standard brackets Longer brackets for recessed mounting (2 inches / 5 cm) Threaded hole in front (1xM10) for clamps Threaded holes on the bottom (4xM5) for 50x100mm VESA plates Selectable fan modes for quiet or cool operation Dimensions (WxDxH): 440 x 43.2 x 400 mm Weight: 6.75Kg (14.87lb)

CONFEZIONE

Altri cavi inclusi · M4250-26G4F-PoE++ (GSM4230UP)· Power cord(s)· Console USB Type-C and RJ45-DB9 cables· Rackmounting standard brackets· Longer brackets for recessed mounting· Rubber footpads for tabletop installation· Installation guide

Software · M4250-26G4F-PoE++ (GSM4230UP)· Power cord(s)· Console USB Type-C and RJ45-DB9 cables· Rackmounting standard brackets· Longer brackets for recessed mounting· Rubber footpads for tabletop installation· Installation guide

Manuali · M4250-26G4F-PoE++ (GSM4230UP)· Power cord(s)· Console USB Type-C and RJ45-DB9 cables· Rackmounting standard brackets· Longer brackets for recessed mounting· Rubber footpads for tabletop installation· Installation guide

Kit e accessori Vari · M4250-26G4F-PoE++ (GSM4230UP)· Power cord(s)· Console USB Type-C and RJ45-DB9 cables· Rackmounting standard brackets· Longer brackets for

recessed mounting·

Rubber footpads for tabletop installation·

Installation guide

SOLUZIONI

Digital Signage

Si