

tesa[®] Powerbond UNIVERSAL



BNR 58565

Product Features

- Perfect for light and flat object in the office
- Ideal for interior use
- Easy to apply

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|--------------------|---------|
| • Total thickness | 1150 µm | • Type of adhesive | acrylic |
| • Backing material | PE foam | | |

Properties/Performance Values

- | | | | |
|---------------------------|-----------------------------------------------------------|-------------------------------|-------------------------------------------|
| • Applicationfield | Bedroom, Children's room, Hall, Home, Living room, Office | • Temperature resistance max. | 40 °C |
| • Chemical resistance | no | • Temperature resistance min. | 10 °C |
| • Residue free removal | no | • Suitable surfaces | Tiles, Most plastics, Glass, Metal, Steel |
| • Application temperature | -10 °C | • Ageing resistance (UV) | yes |

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=NaN>