



Dry



Wet



Heat



Oily



Cold



Chemical



TG6010

A comfortable and flexible seamless knitted glove with X-Dura PU palm dipped coating. Level F cut protection, the highest rating as per the new EN388:2016. For use in dry environments with high cut risk.

Key Features

- Highest level of cut protection according to EN388:2016
- Impressive comfort, dexterity and flexibility
- Seamless knitted 15 gauge liner for enhanced breathability

Ideal for

- Assembly
- Automotive
- Metal fabrication / stamping
- Glass manufacturing
- Construction and Utility
- Aerospace



Sizes:	6-12	Gauge:	15gg
Liner:	HPPE, Steel, Polyamide, Elastane	Coating:	X-Dura PU
No/Bag:	10	No/Carton:	100



TG6010

Glove Specifications

Glove lengths
220mm-270mm

Glove Weight
15 gauge

Liner Type
HPPE/Steel/Polyamide/Elastane

Glove colour
Pantone 368c / R:92 G:193 B:81 / C:63 M:0 Y:100 K:0

Overlock Colours

SIZE	XS-6	S-7	M-8	L-9	XL-10	2XL-11	3XL-12
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK	GREEN

Coating Specifications

Coating colour
Black

Dip type
X-Dura Polyurethane

Dip Application
Palm Dipped

Glove Treatment
X-Dura



Packaging Information

Qty/bag
10 pairs

Qty/carton
100 pairs

Carton Dimensions
300mm x 600mm x 200mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.