

# EC Safety Data Sheet

in accordance with 91/155/EEC



Page1 of 4

Schwan-STABILO Safety Data Sheet 84X / 3 (engl.)

Revised : 16. Oct. 2008

**1. TRADE NAME :** ink for STABILO OHPen universal 13/..  
**Art.-No. 841 / ..; 842/..; 843/ ..;**

### Supplier Details

Schwan-STABILO  
Schwanhaeusser GmbH & Co. KG  
Schwanweg 1, D-90562 Heroldsberg, Germany  
Telephone: Germany (++49) 911 / 567-4575 or (++49) 911 – 398 24 51

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

Lower alcohols < 80% (F, Xi, R11, 41, 67); n-Butanol < 6% (CAS: 71-36-3) R 10, 22, 37/38, 41, 67;  
13/36 contains <5% Basic Green 1 (Xn, N R22, 50/53) and <4% Solvent yellow 146 (Xi, R36, 43, 51/53)  
13/41 contains <4% Basic Blue 7 (T, N R25, 41, 50/53)  
13/45 and 13/55 contain < 6% Basic Violet 10 (Xi, R41, 52/53)

## 3. HAZARDS IDENTIFICATION

Easily Inflammable. May form explosive mixture with air, particularly in empty uncleaned containers. Heating causes rise in pressure - increased danger of bursting and explosion.

## 4. FIRST-AID-MEASURES

In case of inhalation: Provide fresh air. Keep the person affected warm and lying comfortable. In case of complaints seek medical attention.

Immediately remove any clothing which has been soaked with the solution.

In case of contact with open eye: Rinse thoroughly with plenty of water and contact an ophthalmologist.

In case of swallowing: Only if person affected is fully conscious, make him-/herself vomit and consult a doctor.

The following symptoms may occur in case of inhalation over extended period: Headache, nausea, dizziness, weakness, unconsciousness.

## 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray jet, alcohol-resistant foam, sand gaseous extinguishing media, dry powder extinguisher.

Not to use : strong water jet

Cool containers affected with water spray jet.

In case of fire, possible release of carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitric oxides (NO<sub>x</sub>).

## 6. ACCIDENTAL RELEASE MEASURES

Ensure sufficient ventilation. Keep ignition sources away. Absorb in liquid-binding material(e.g. universal binding agent, kieselguhr, expanded mica). Dispose of saturated binding material in compliance with local public authority regulations.

Wash away any residue with water.

Revised : 16. Oct. 2008

**7. HANDLING AND STORAGE**

Keep containers tightly closed and store in a cool place. Heating causes rise in pressure - and danger of bursting. Ensure good ventilation of room also at ground level (fumes are heavier than air). Take measures to prevent electrostatic charging. Explosive mixtures may form in emptied drum.

The products are classified Class B, according to the German "VbF" (Regulation for Flammable Liquids) – therefore the allowed amount for storage, according to the German "TRbF 110" (Technical Rules for flammable Liquids) must be observed.

**8. EXPOSURE CONTROL / PERSONAL PROTECTION**

Breathing mask in case of high concentrations. For short periods filter equipment, filter A. Gloves (solvent-resistant, e.g. Latex, Chloroprene) Closely fitting protective goggles.

General protection and hygiene measures: Observe the usual precautions for handling chemicals. Do not inhale fumes over long period.

Do not eat and drink at work. Do not smoke at work. After work and before breaks thoroughly clean exposed skin.

**9. PHYSICAL AND CHEMICAL DATA**

Form	:	liquid	
Colour	:	depending, as per shade	
Odour	:	characteristic, alcohol-type	
Boiling Point	:	78	°C
Flash Point	:	13	°C (DIN 51755)
Ignition Temperature	:	> 400	°C (DIN 51794)
Explosion Range (lowest)	:	1.6	Percent (v/v)
Vapour Pressure	:	5.9	kPas
Density	:	app. 0.85	g/cm <sup>3</sup>
Solubility in Water	:	unlimited miscibility	
Solubility in other Solvents	:	soluble in many organic solvents	
pH-Value	:	not applicable	
Viscosity	:	< 7	mPas

**10. STABILITY AND REACTIVITY**

Thermal Decomposition	:	Reaction with strong oxidizing agents. Reaction with alcali metals and with-alcaline earth metals. Development of inflammable vapours.
Hazardous Reactions	:	None, if stored and handled properly.
Hazardous Decomposition Products	:	In case of fire, release of carbon monoxide (CO), carbon dioxide CO <sub>2</sub> ) and nitric oxides(NO <sub>x</sub> ).

Schwan-STABILO Safety data Sheet 84X / 3 (engl.)

Revised : 16. Oct. 2008

**11. TOXICOLOGICAL INFORMATION**

Acute oral Toxicity (LD <sub>50</sub> )	:	No information available.
Irritant Effects on		
Skin	:	No information available
Mucous Membranes	:	In high concentrations irritation of nose eyes and mucous membranes possible. In case of contact with eyes, severe, reversible irritation due to alcohol content.
Empirical Knowledge	:	The product discolours the skin. Inhalation of high concentrations causes narcotic effect/intoxication. Resorption possible after affecting gastro-intestinal tract.

**12. ECOLOGICAL INFORMATION**

Fish Toxicity	:	Poisonous effect on fish and plankton possible. Do not allow to enter sewage works or inland waters.
Further Ecological Advises	:	The product is biodegradable. The dyes can be sufficiently eliminated from the water by absorption in activated sludge. The biodegradability of the product has not been tested. The above statements were derived from products of similar composition.

**13. DISPOSAL CONSIDERATION**

May be added to household waste in small quantities. Larger quantities are to be disposed of under compliance with local public authority regulations at a suitable waste disposal site or incinerator.

Contaminated packaging has to be emptied completely and may be recycled after thorough cleaning..

**14. TRANSPORT INFORMATION**

<b>ADR/RID</b>	:	Class 3	UN-No. :	1263	PG :	II
Proper Shipping Name	:	<b>PAINT</b>				
		<b>UN 1263 PAINT, 3, II</b>				
<b>IMDG-Code</b>	:	Class 3	UN-Nr. :	1263	PG :	II
EmS	:	F-E, S-E				
Marine pollutant	:	No				
Proper Shipping Name	:	<b>PAINT</b>				
		<b>FARBE</b>				
<b>IATA-DGR</b>	:	Class 3	UN/ID-No.:	1263	PG :	II
Proper Shipping Name	:	<b>Paint</b>				

Schwan-STABILO Safety Data Sheet 84X / 3 (engl.)

Revised : 16. Oct. 2008

**14. TRANSPORT INFORMATION (continued)**

The transport informations are cited according to international regulations and the way they are used in Germany (GGVE/GGVS). Possible divergence in other countries was not taken in consideration.

**15. REGULATORY INFORMATION****Labelling in accordance with EC hazard warning labelling compulsory / GefStoffV**

Classification	:	Easily inflammable F (flame)
Hazard Symbols	:	Xn (harmful) (84X/ 41 blue ink) Xi (irritant) (84X/36,45,55 green, brown, Violet) N (dangerous for the environment) (84X/41,45 Blue, brown)
R-Phrases	:	11 (all colours) 22 (84X/41 blue) 36 (84X/36,45,55 green, brown, violet) 51-53 (84X/41,45 blue, brown) 52-53 (84X/36, 46)
S-Phrases	:	2-7-16-24/25-46-61

**National Regulations**

VbF	:	B
Water Hazard Class Wassergefährdungsklasse (WGK)	:	1, 2, 3 (self-classification)

**The shades are classified as follows:**

**WGK 3: Art.-No. 84X/46**

**WGK 2: Art.-No. 84X/36,41,45**

**WGK 1: Art.-No. 84X/18,40,55,56**

**16. OTHER INFORMATION**

The information in item 3 to 8 and 10 to 12 does not refer to the correct use of the commercial product (cf. product information and usage instructions) but to the release of larger quantities of the product through accidents or other irregularities.

Vertical lines in the right-hand margin of this safety data sheet indicate changes from the previous version.

The above information is based on our present state of knowledge. It should not therefore be construed as guaranteeing specific properties of the products describes or their suitability for a particular application.