

Status: 22.09.2008

	nk (blue)	
Use of the substance	e/preparation	
Company/undertaking	g identification	
Bookkoppel 7		
Telephone no.	+49 (0) 41 02 / 80 8-0	
Information provided +49 (0)4102 - 808-0	d by / telephone	
Advice on Safety Da sdb_info@umco.de	ta Sheet	
Hazards identifica	tion	
	lish's flower ship	
R66	Repeated exposure may cause skin dryness or cracking.	
Hazard symbols		
	Highly flammable	
-	Highly flammable	
66		
67	Vapours may cause drowsiness and dizziness.	
Composition / info	rmation on ingradiants	
Concentration	> 20 < 40 %-b.w.	
Classification	F; R11 Xn; R65	
	F, Xn R phrases 11-65	
EC no.	236-675-5 Index no CAS no. 13463-67-7	
	> 10 < 20 %-bw	
Concentration	> 10 < 20 /0-D.W.	
Concentration Classification Hazard symbols	- R phrases -	
	Company/undertal   Identification of the substance   Trade name   Paint Marker I   contained in:   Use of the substance   Ink for use in drawlin   Company/undertaking   Address   edding Aktiengesells   Bookkoppel 7   D-22926   Ahrensb   Telephone no.   Information provided   +49 (0)4102 - 808-0   Emergency telephone   +49 (0)30 192 40 (To   Advice on Safety Da   sdb_info@umco.de   Hazards identification   F; R11   R67   R66   Hazard symbols   F   R phrases   11   66   67   Chemical characteriza   Mixture (preparation)   Hazard symbols   F   R phrases   11   66   67   Chemical characteriza   Mixture (preparation)   Hazard symbols   TITANIUM DIOXIDE   EC no.	Paint Marker Ink (blue) contained in: edding 750, edding 751, edding 780 paint marker   Use of the substance/preparation Ink for use in drawliners   Company/undertaking identification   Address edding Aktiengesellschaft Bookkoppel 7 D-22926 Ahrensburg Telephone no. +49 (0) 41 02 / 80 8-0   Information provided by / telephone +49 (0)3192 40 (Toxic Substance Emergency Call Centre Berlin)   Advice on Safety Data Sheet sdb_info@umco.de   Hazards identification   Classification F, R11 Highly flammable R67 Vapours may cause drowsiness and dizziness. R66 Repeated exposure may cause skin dryness or cracking.   Hazard symbols F Highly flammable. 66 Repeated exposure may cause skin dryness or cracking.   Composition / Information on ingredients Composition / Information on ingredients Classification F F. N1 Highly flammable. R67 CAS no. 1678-91-7 Concentration   Mixture (preparation) Hazard symbols F, X1 X1, R65 Hazard symbols F, Xn R phrases 11-65   ET HYLCYCLOHEXANE E TO 0. 20 40 %-b.w. Classification F, Xn R phrases 11-65   ET ANNUM DINDIE E. Cono 28-675-5 Index no. CAS no. 13463-67-7

Trade name: Paint Marker Ink (blue)

Version: 1.0.0 / GB

#### NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

265-150-3 649-327-00-6 CAS no. 64742-48-9 FC no Index no. Concentration 10 30 %-b.w. > < Xn; R65 R67 Classification F: R11 R66 Hazard symbols F, Xn 11-65-66-67 R phrases

#### Other information (chapter 3.)

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

#### 4.) First aid measures

#### **General information**

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

#### After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

#### After skin contact

Wash off immediately with soap and water.

#### After eye contact

Separate eyelids, wash the eyes thoroughly with water (15 min.).

#### After ingestion

Rinse mouth thoroughly with water. Summon a doctor immediately. Never give anything by mouth to an unconscious person.

#### 5.) <u>Fire-fighting measures</u>

#### Suitable extinguishing media

Foam; extinguishing powder; Carbon dioxide

Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

In the event of fire, the following can be released: Carbon dioxide (CO2) Carbon monoxide (CO)

#### Special protective equipment for fire-fighters

Use self-contained breathing apparatus. Wear protective clothing.

#### Other information

Cool endangered containers with water spray jet. Suppres gases/vapours/mists with water spray jet.

#### 6.) Accidental release measures

#### **Personal precautions**

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away sources of ignition.

#### **Environmental precautions**

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

#### Methods for cleaning up/taking up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When picked up, treat material as prescribed under heading "Disposal considerations".

#### 7.) Handling and storage


#### Handling

#### Advice on safe handling

Provide good ventilation of working area (local exhaust ventilation, if necessary). Product inherent



Trade name: Paint Marker Ink (blue)





Status: 22.09.2008

handling risks must be minimised taking the appropriate measures for protection and preventive actions. The working process should be designed to rule out the release of hazardous substances or skin contact as far it is possible by the state of the art.

#### Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

#### Storage

#### Requirements for storage rooms and vessels

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Always keep in containers of same material as the original one.

#### Advice on storage assembly

None known

#### Further information on storage conditions

Keep container tightly closed in a cool, well-ventilated place. Protect from heat and direct sunlight.

#### 8.) Exposure controls / personal protection

# Exposure limit values

CAS no.	13463-67-7
EC no.	236-675-5
Occupational Exposure	e Standards (OESs) / EH40
Titanium dioxide	
total inhalable dust	

TWA 10 mg/m<sup>3</sup>

Occupational Exposure Standards (OESs) / EH40 Titanium dioxide

respirable dust TWA 4 mg/m<sup>3</sup>

#### Personal protective equipment

#### **Respiratory protection**

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

#### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective glove should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

#### Eye protection

Safety glasses with side protection shield (EN 166)

#### Skin protection

Clothing as usual in the chemical industry.

#### General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Have eye wash fountain available. Have emergency shower available.

Trade name: Paint Marker Ink (blue) Version: 1.0.0 / GB

# edding

Status: 22.09.2008

		_		
9.)	Physical and chemical p General information Form Colour Odour	liquid blue aromatic		
	Important health, safety and	environmental info	ormation	
	<b>Changes in physical state</b> Type Value	Boiling point	116	Э
	<b>Flash point</b> Value		7	c
	<b>Ignition temperature</b> Value	200	- 262	°C
	Explosion limits			
	Upper explosion limit	8,40		% vol
	Lower explosion limit	0,90		% vol
	Vapour pressure Value Reference temperature	28	10 °C	mm Hg
	<b>Density</b> Value Reference temperature	20	0,96 °C	g/cm³
	<b>Viscosity</b> Type Value	dynamic	2300	mPa*s
	Solubility in water Remarks	insoluble		
10.)	Stability and reactivity			
	Conditions to avoid Heat			
	Materials to avoid None known.			
	Hazardous decomposition pr No hazardous decomposition			
11.)	Toxicological informatio	<u>n</u>		
	Experience in practice Inhalation of vapours may lea Repeated and prolonged skin skin. Eye contact with the product	n contact may cause	e removal of	d dizziness. natural fat from the skin and irritation of the
	Other information (chapter 1 Product specific toxicologica	l.)		

Trade name: Paint Marker Ink (blue) Version: 1.0.0 / GB



Status: 22.09.2008

#### 12.) <u>Ecological information</u>

#### Other adverse effects

Ecological data are not available. Do not discharge product unmonitored into the environment.

#### 13.) Disposal considerations

#### Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

#### Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

#### 14.) <u>Transport information</u>

Land transport ADR/RID Class Packaging group Hazard id. no. Label UN number Technical name Special Provision 640	3 II 33 3 1263 Paint D	Classification code	F1
Marine transport IMDG Class Packaging group UN number Proper shipping name EmS MARPOL Label	3 II 1263 Paint F-E,S-E - 3		
Air transport ICAO/IATA Class Packaging group UN number Proper shipping name Label	3 II 1263 Paint 3		

#### 15.) <u>Regulatory information</u>

Labelling in accordance with EC directives The product is classified and labelled in accordance with EC Directive 1999/45/EC. The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

Hazard symbols F	Highly flammable
R phrases	
11	Highly flammable.
66	Repeated exposure may cause skin dryness or cracking.
67	Vapours may cause drowsiness and dizziness.

Trade name: Paint Marker Ink (blue) Version: 1.0.0 / GB

#### S phrases

24	Avoid contact with skin.
37	Wear suitable gloves.

Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances

Remarks

Annex I, part 2, category 7 b

#### 16.) Other information

#### Sources of key data used to compile the data sheet:

EC Directive 67/548/EC resp. 99/45/EC as amended in each case. Regulation (EC) No 1907/2006 (REACH) as amended in each case. EC Directives 2000/39/EC, 2006/15/EC as amended in each case. National Threshold Limit Values of the corresponding countries as amended in each case. Transport regulations according to ADR, RID, IMDG, IATA as amended in each case. The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

#### Relevant R-phrases (chapter 3):

11	Highly flammable.
65	Harmful: may cause lung damage if swallowed.
66	Repeated exposure may cause skin dryness or cracking.
67	Vapours may cause drowsiness and dizziness.

#### Department issuing safety data sheet

UMCO Umwelt Consult GmbH

Georg-Wilhelm-Str. 183 b, D-21107 Hamburg

Tel.: +49 40 / 41 92 13 00 Fax: +49 40 / 41 92 13 57 e-mail: umco@umco.de

This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.

.