

	Ref. STD	Unit of meas.	TECHNICAL SPECIFICATIONS			
Substance	ISO 536	g/m2	80			
Caliper	ISO 534	µm	104,0			
Bulk	ISO 534	cm3/g	1,30			
Roughness Bendtsen	ISO 8791-2	ml/min	250,0			
Brightness ISO	ISO 2470 (D65)	%	112,0			
Opacity ISO	ISO 2471	%	92,0			
Whiteness	ISO 11475	%	161,0			

Tolerances	Ref. STD	Unit of meas.	RANGE			
Substance	ISO 536	g/m2	78.0/82.0			
Caliper	ISO 534	µm	100.0/108.0			
Bulk	ISO 534	cm3/g	-			
Roughness Bendtsen	ISO 8791-2	ml/min	200/300			
Brightness ISO	ISO 2470 (D65)	%	110.0/114.0			
Opacity ISO	ISO 2471	%	90.0/94.0			
Whiteness	ISO 11475	%	158.0/164.0			



Quality Management System Certification  
n. SGS-IT 95/0027.02



Environmental Management System Certification  
SGS-IT 14/0628.04



100% recyclable



Elemental chlorine free



ISO 9706  
Permanent paper



The mark of responsible forestry

**Notes:** - FSC Mix Credit Uncoated Paper-Only the products that are identified as such on this document are FSC® certified

Finishing **Uncoated**

Printing method **Inkjet - Laser**

Applications **Laser printers (colour) - Copiers - Inkjet printers (colour) - Inkjet printers (black & white) - Laser printers (black & white) - Multifunction Copiers**

Values referred to each quality are to be considered as reference data and could change without notice. Each value is subject to trade tolerances.