



Sorgente luminosa
Light source



Materiale

Alluminio

Colore

Nero

Sorgente luminosa

LED SMD 100W - 150W - 200W

Flusso luminoso

14000 Lm - 21000 Lm - 28000 Lm

Driver

Incluso

Temperatura colore

4000K

Durata e on/off

50.000h >25.000 on/off

Angolo di luce

110°

CRI

>80

Grado IK

IK10

Material

Aluminium

Colour

Black

Light source

LED SMD 100W - 150W - 200W

Luminous flux

14000 Lm - 21000 Lm - 28000 Lm

Driver

Included

Color temperature

4000K

Lifetime and on/off

50.000h >25.000 on/off

Beam angle

110°

CRI

>80


IK degree

IK10




LED-STARGATE-100XP 100W - 14000 LM PF 0,90
8031414877799

Misure - size
dimensioni in mm -
size mm




LED-STARGATE-150XP 150W - 21000 LM PF 0,90
8031414877805

Misure - size
dimensioni in mm -
size mm




LED-STARGATE-200XP 200W - 28000 LM PF 0,90
8031414877812

Misure - size
dimensioni in mm -
size mm




Fotometria del Prodotto


Photometric curve of the product



LED-STARGATE-100XP



LED-STARGATE-150XP



LED-STARGATE-200XP