

Material Safety Data Sheet

Toner Type: PT071

For Models: B410, B430, B440

B2200, B2400 B4400, B4600



Material Safety Data Sheet

SECTION 1 -Chemical Product and Product Company Identification _____

Product name : PT071

Manufacturer: Address: Telephone Number:
Oki Data Corporation 4-11-22 Shibaura, 81-3-5445-6106
Minato-ku, Tokyo Fax Number:
108-8551, Japan 81-3-5445-6177

SECTION 2 -Composition / Information on Ingredients _

HAZADOUS INGREDIENTS	CAS#	AMOUNT	EXPOSURE LIMIT			
HAZADOUS INGREDIENTS	CAS#	AMOUNT	OSHA	APEL	ACGII	H TLV
Carbon black (bound)	1333-86-4	4-8 %	3.5 ppm	TWA	3.5 ppm	TWA
Chamara	100.49.5	< 70	50 ppm	TWA	20ppm	TWA
Styrene	100-42-5	<50ppm	100 ppm	STEL	40 ppm	STEL,A4

OTHER INGREDIENTS	CAS#	AMOUNT	NOTES
Styrene acrylate copolymer	25767-47-9	70-90 %	TWA-Time Weighted Average TLV-Thrashold Limit Value AL-Action Level RD-Respirable Dust TD-Total Dust
Fatty acid ester	75587-84-7	0-2.5 %	STEL-Short Term Exposure Limit Skin-Skin contact may
PMMA	9011-14-7	0-3 %	be a significant route of exposure A1-Confirmed Human Carcinogen A2-ACGIH Suspected Human Carcinogen
Silicon Diocide(amorphous)	67762-90-7	0-5 %	A3 — ACGIH Animal Carcinogen A4 — ACGIH Not Classifiable as a Human Carcinogen PNOC — Particulates Not Otherwise classified

EMERGENCY OVERVIEW

This product is the black colored toner with an odorless. As supplied, these products are not expected to cause any adverse health or physical effects in how to use usual. Processing operations may produce vapors or dust that may cause eye, skin and respiratory tract irritation. Tonic combustion products may be released under fire conditions.

SECTION 3 - Hazards Identification _____

Potential Health Effects From Overexposure: Possible routes of entry include skin & eye contact and process vapor or dust inhalation. Minimal respiratory tract irritation may occur as with exposure to large amount of any non-tonic dust. We recommend that contact with exposed skin be avoided by the use of gloves and other personal protective equipment appropriate for handling and / or processing operations. Over exposure to decomposition or combustion products may cause imitation of the eyes, skin, and respiratory tract.

See Section 10 for information on combustion products.

SECTION 4 - First And Measures _____

If irritation occurs or persists from any route of exposure, remove the affected individual from the area and seek medical assistance.

Eye Contact: Eye irritation will be cased. If contacted, Flush eyes with running water for 15 minutes with eyelids open. Consult an eye-doctor.

Skin Contact: No symptoms will appear. If contacted, remove contaminated clothes an wash skin with soap and water.

Particulate Inhalation: Lung irritation, difficult breathing, sneezing, coughing, will be caused. If inhaled, remove the sufferer to fresh air and seek medical assistance immediately.

Ingestion: Stomach irritation will be caused. If ingested, seek medical assistance immediately.

SECTION 5 - Fire Fighting Measures	
------------------------------------	--

Extinguishing Media: Dry chemicals, CO2, water spray or foam are recommended media.

Special Firefighting Procedures: Do not use straight water, high-pressure water or water steam in order to prevent creating a dust cloud and spreading fire dust. Use appropriate respirator for carbon monoxide and carbon dioxide. Wear positive pressure self-contained breathing apparatus (SCBA) during the attack phase of firefighting operations and during cleanup in enclosed or poorly ventilated areas immediately after a fire. Personnel not having suitable respiratory must leave the area to significant exposure to toxic combustion gases from any source.

Unusual Fire and Explosion Hazards: Thermal decomposition of organic components may result in occurrence of oxides of carbon. Special precautions must be taken if like most organic materials in powder form, it form explosive mixtures when dispensed in air. Toxic gases may be formed upon combustion and represents a hazard to fire fighters. See Section 10 for additional information on combustion products.

Explosion limits: Lower – 60g/m3 (for powder)

SECTION 6	- Accidental Release Measures	
DEPOTION 0	- Accidental Nelease Measures	

Sweep the spilt toner or remove it with a vacuum cleaner, and transfer into the sealed container carefully. Sweep slowly to minimize generation of dust during clean-up. If the vacuum cleaner is used, the motor must be rated as dust explosion-proof. A conductive hose bonded to the machine should be used to reduce static buildup. Residue can be removed with soap and cold water. Clothes may be washed or dry cleaned after removal of loose toner.

SECTION 7 - Handling And Storage	
----------------------------------	--

Handling: Keep out of the reach of children. In case of accidental spill, try not to disperse the particles. Avoid prolonged inhalation of excessive dust and contact eyes. Use with adequate ventilation. Use the mask, which recommended preventing dust and coarse particulate.

Storage: Keep out of the reach of children. Keep container tightly closed. Keep away from contact with oxidizing materials. Store in a cool and dry place away from direct light to maintain quality.

SECTION 8 - Exposure Controls / Personal Protection

Ventilation: Effective general and, if necessary, local exhaust ventilation must always be provided to draw fumes or vapors away from workers to prevent routine inhalation.

Ventilation must be adequate to maintain the ambient workplace atmosphere below the limits listed in Section 2

Local Exhaust: Recommended Mechanical (General): Recommended

Respiratory Protection: Respiratory protection is not typically required during normal use and handling operations where general dilution ore local exhaust ventilation is adequate to control exposures. Not required under normal conditions. For use other than in normal operating procedures (such as in the event of large spill), goggles and respirators may be required.

Protective Equipment: Use the mask, which recommended preventing dust and coarse particulate, and goggles when handling a large quantity of toner or during long-term exposure, as with any non-toxic dust. Protective gloves should be worn to prevent skin contact.

Eye/face: safety goggles Skin: Protective gloves recommended

Respiratory: Dust mask (Respirator for large spill)

SECTION 9 – Physical and Chemical Properties				
Specific Gravity (H2O-1): 1.15 Appearance and Odor: Clack Powder and Odorless	Solubility in Water: Negligible			
SECTION 10 – Stability and Reactivity				

Conditions to Avoid: Overheating (Do not expose to temperature above 200°C) and contact with ignition sources such as open flames, sparks, electrical arcs and static discharge sources.

Hazardous Polymerization: Will not occur

Materials to Avoid: Avoid exposure to strong oxidizers or reducing agents.

Hazardous Decomposition Products:

Stability: Stable

The gas generated by heat decomposition may contain carbon monoxide, carbon dioxide and Nitrogen.

SECTION 11 - Toxicological Information

Health Hazards (Acute and Chronic):

Acute Oral Toxicity: LD50>2000mg/kg (Rat)
Acute Inhalation Toxicity: LC50>4.98mg/kg (Rat)

Skin Irritation: No irritant (Rabbit)
Eye Irritation: Minimal irritant (Rabbit)
Mutagenicity: Negative (Ames Test)

Carbon Black

Carcinogenicity:

In 1998, the IARC reevaluated carbon black as a Group 28 carcinogen (possible human carcinogen). This classification is given to chemicals for which there is inadequate human evidence, but sufficient animal evidence on which to base an opinion of carcinogenicity. The classification is based upon the development of lung humors in rats receiving chronic inhalation exposures to free carbon black at levels that induce particle overload of the lung. Studies performed in animal models other than rats did not show any association between carbon black and lung tumors. Moreover, a two-year cancer bioassay exposure and tumor development in rats.

SECTION 12	Ecological Information	
No information a	available.	
SECTION 13	- Disposal Consideration	
	e appropriate Sate and Local Was	Regulation 40 CFR 261 when disposed. See Authorities for additional information. Incinerate
SECTION 14	- Transport Information	
_		not defined or designated as a hazardous material by 49 of the Code of Federal Regulations.
SECTION 15	Regulatory Information	
Inventories:	JCSCL (Japan) Yes TSCA (USA) Yes EUBECS/ELINCS (EU) Yes	

Hazard Rating System Classifications:

-Other Information

SECTION 16

	NFPA	HNIS	Key: 0=least; 1=slight: 2=moderate; 3=high; 4=extreme	
Health	1	1	National Fire Protection Association rating identific hazards during a fire emergency.	
Flammability	1	1	Hazardous Materials Identification System rating applies	
Reactivity	0	0	to products as packaged.	

DATE ISSHUED: October, 2005 (Page 5 of 5)

Appendex A - Carbon black

This product contains trace Carbon black. Carbon black is listed by the international Agency for Research on Cancer (IARC) as a Group 28 carcinogen (possibly carcinogenic to humans).

User's Responsibility

This bulletin cannot over all possible situations, which the user may experience during processing. Each aspect of your operation must be examined to determine if, or where, additional precautions may be necessary.

All health and safety information contained in this bulletin must be provided to your employees or customers. It is your responsibility to use this information to develop appropriate work practice guidelines and employee instructional programs for your operation.

Disclaimer of Liability

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this material. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazardous connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local laws and regulations remains the responsibility of the user.