

Technical Specifications

Self-Retracting Lifeline FALCON

<u>Description</u>: The self-retracting lifeline Falcon range is the safest, most robust range of composite retractable lifelines on the market.

References:

1011950: Falcon 10 m galvanized steel cable 1013582 : Falcon 20 m galvanized steel cable

Features:

- hight quality, corrosion resistance components
- quick-activating braking mechanism stops the fall
- no annual factory re-certification required**
- 1 swivel mounted with a snap hook 18 mm
- lightweight, robust composit unit (torsion relieved)

Tested and approved for horizontal applications (When used with locking karabiner and a 1m steel anchorage sling)

**The CE standard requires inspection by a trained end-user competent person, following the Miller Repair Guide.



35-37 rue de la Bidauderie F - 18100 Vierzon - France Tel: +33 2 48 52 40 40

Fax: +33 2 48 71 04 97 Web site: www.honeywellsafety.com



Housing: Hight-Impact Nylon

Hub: Heat Treated Aluminium

Breaking Mechanism: Stainless Steel and Bronze

Cable Lifeline: Ø 4.5 mm Galvanized Steel

Swivel at the bottom of the cable = Stainless steel

Snap hook 18 mm: Steel

Weight: 5kgs

Dimension: 255 x 213 x 101 mm Temperature: -30°C to +50°C Breaking Strenght: 12 KN

EN 360



The cable is now supplied with double ferrule

LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

35-37 rue de la Bidauderie F - 18100 Vierzon - France Tel : +33 2 48 52 40 40

Fax: +33 2 48 71 04 97 Web site: www.honeywellsafety.com