



Dry



Wet



Heat



Oily



Cold



Chemical



# TG6010

A comfortable and flexible seamless knitted glove with X-Dura PU palm dipped coating. Level F cut protection, the highest rating as per the new EN388:2016. For use in dry environments with high cut risk.

## Key Features

- Highest level of cut protection according to EN388:2016
- Impressive comfort, dexterity and flexibility
- Seamless knitted 15 gauge liner for enhanced breathability

## Ideal for

- Assembly
- Automotive
- Metal fabrication / stamping
- Glass manufacturing
- Construction and Utility
- Aerospace

<b>Sizes:</b>	6-12	<b>Gauge:</b>	15gg
<b>Liner:</b>	HPPE, Steel, Polyamide, Elastane	<b>Coating:</b>	X-Dura PU
<b>No/Bag:</b>	10	<b>No/Carton:</b>	100



# TG6010

## Glove Specifications

**Glove lengths**  
220mm-270mm

**Glove Weight**  
15 gauge

**Liner Type**  
HPPE/Steel/Polyamide/Elastane

**Glove colour**  
Pantone 368c / R:92 G:193 B:81 / C:63 M:0 Y:100 K:0

## Overlock Colours

SIZE	XS-6	S-7	M-8	L-9	XL-10	2XL-11	3XL-12
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK	GREEN

## Coating Specifications

**Coating colour**  
Black

**Dip type**  
X-Dura Polyurethane

**Dip Application**  
Palm Dipped

**Glove Treatment**  
X-Dura



## Packaging Information

**Qty/bag**  
10 pairs

**Qty/carton**  
100 pairs

**Carton Dimensions**  
300mm x 600mm x 200mm

## Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

## Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

## Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.