

tesa[®] Signal Universal



BNR 58133, 58134

Product Features

- Strong PP backing
- Solvent-free adhesive with high UV-resistance
- For marking permanent obstacles and hazard areas
- Even, low-noise unwinding
- Colour code according to EU regulation for marking
- Suitable for use in all tesa[®] hand dispensers

Product Description

tesa[®] Signal universal is a multi-purpose marking tape to permanently mark obstacles and hazardous areas. It is available in two color codes.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|--------------------|---------------------|
| • Total thickness | 52 µm | • Type of adhesive | water-based acrylic |
| • Backing material | PP film | | |

Properties/Performance Values

- | | | | |
|------------------------|-------------------------|---------------------|---------------------------------|
| • Applicationfield | Home, Garden,
Office | • Suitable surfaces | Even wood, Plaster,
Concrete |
| • Tensile strength | 37 N/cm | • Adhesive strength | High adhesion |
| • Residue free removal | no | • Solvent free | yes |
| • Hand tearability | no | • Tear resistance | no |

tesa[®] Signal Universal

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=58133>